



Tagalong 5 Ton Series

• G.V.W.R.- 9950#	• Axles - 2-5,000 # cambered brake axles
• G.A.W.R.(Each Axle) - 5200 #	• Suspension - Multi-leaf spring with equalizer
• Coupler - 2"- 5/16 adjustable	• Tires - 225-75-15" load range D
• Safety chain - 8/0 grade 30 with hooks	• Wheel - 15 " 5 bolt white spoke
• Jack - top wind	• Deck - 2" pressure treated pine
• Frame - 8" I-Beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 3" Angle 2" x 3" x 3/16"	• Elec. Plug - 7-way RV
• Ramps- 6' slide out	• Paint - High solids acrylic enamel

Standard Features

Optional Features

• Crossmembers on 16" centers	• Steel deck
• Sealed modular wiring harness	• D-Rings
• Electric breakaway	• Tool tray in tongue
• E-Z Lube axles	• Spare tire rack under body
• 6' Ramps slide out	• 10K Jack

Dimensions

Weight / Length	A	B	C	D	E
2,500Lbs / 16'	192"	113.25"	51.25"	30.5"	102"
2,600Lbs / 18'	216"	125.25"	51.25"	30.5"	102"
2,700Lbs / 20'	240"	137.25"	51.25"	30.5"	102"

