



Tagalong 6 Ton Series

| | |
|--|--|
| • G.V.W.R. - 12,000 # | • Axles - 2 Dexter 6,000 # single wheel electric brake axles |
| • G.A.W.R. (Each Axle) -6,000 # | • Suspension - Multi-leaf spring with equalizer |
| • Coupler - 3 position adjustable | • Tires - ST 235/80R 16" Load Range E |
| • Safety Chain - 3/8" grade 43 with hooks | • Wheel - 6.75 x 16" 8 bolt white spoke |
| • Jack - 10,000 # drop leg | • Deck - 2" pressure treated pine |
| • Frame - 8" channel | • Lights - D.O.T. stop, tail, turn, and clearance |
| • Crossmembers - 3" channel on 16" center | • Elec. Plug - 7-way RV |
| • Side rails - 6" channel w/stake pockets /rub rails | • Paint - High solids acrylic enamel |

Standard Features

Optional Features

| | |
|---------------------------------|---------------------------|
| • Crossmembers on 16" centers | • Dual jacks |
| • Sealed modular wiring harness | • Steel deck |
| • Electric breakaway | • D-Rings |
| • E-Z Lube axles | • Electric over hydraulic |
| • 5' Dovetail | • 7 ton option |
| • 5' Ramps | • Pop-up dovetail |
| • Tool tray in tongue | • Spring-loaded ramps |

Dimensions

| Weight / Length | A | B | C | D | E | Dove |
|-----------------|------|---------|-----|-----|------|------|
| 5,500Lbs / 25' | 300" | 178.75" | 68" | 37" | 102" | 60" |
| 5,650Lbs / 29' | 348" | 202.75" | 68" | 37" | 102" | 60" |

