



10 Ton Tagalong Series

| | |
|--|--|
| <ul style="list-style-type: none"> • G.V.W.R. - 22,500# • G.A.W.R.(Each Axle) - 10,000# • Coupler -3 position pintle ring • Safety Chain -3/8" grade 43 with hooks • Jack-10,000 # drop leg • Frame -12" I-beam • Crossmembers - 3" channel on 16" center • Side rails - 6" channel w/stake pockets /rub rails | <ul style="list-style-type: none"> • Axles - 2 Dexter 10,000# dual wheel electric brake axles • Suspension-Multi-leaf spring w/equalizer • Tires - ST 235/80R 16" Load Range E • Wheel - 6.75 x 16" dual 8 bolt • Deck - 2" pressure treated pine • Lights - D.O.T. stop, tail, and clearance • Elec. Plug 7-way RV • Paint - High solids acrylic enamel |
|--|--|

Standard Features

Optional Features

| | |
|---|--|
| <ul style="list-style-type: none"> • 16" dual wheels • Crossmembers on 16" centers • Sealed modular wiring harness • Electric breakaway • Oil bath axle • 5' dovetail • 5' ramps • Tool tray in tongue • Rubber mount lights | <ul style="list-style-type: none"> • Popup dovetail • Dual jacks • Boxend tail • Locking tool box • Spring loaded ramps • Air brakes • 12 Ton capacity • Electric over hydraulic • Buck head 6" channel |
|---|--|

Dimensions

| Weight / Length | A | B | C | D | E | Dove |
|-----------------|------|---------|-----|-----|------|------|
| 6,000Lbs / 25' | 300" | 178.75" | 68" | 37" | 102" | 60" |
| 6,300Lbs / 29' | 348" | 202.75" | 68" | 37" | 102" | 60" |
| 6,600Lbs / 31' | 372" | 214.75" | 68" | 37" | 102" | 60" |

