



## Commercial Series TA10TC Tagalong Series Pierced Frame

• G.V.W.R. - 22,500 #	• Axles - 2 Dexter 10,000 # dual wheel electric brake axles
• G.A.W.R.(Each Axle) -10,000#	• Suspension - multi-leaf slipper spring
• Coupler -3 position pintle ring	• Tires - ST235/80R/16" load range D
• Safety Chain -3/8" grade 43 with hooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jack-10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame -12" @ 19# I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 4" channel on 16" center	• Elec. Plug 7-way RV
• Side rails - 8"channel with (10) D-rings	• Paint - high solids acrylic enamel

### Standard Features

### Optional Features

• 16" dual wheels	• Dual jacks
• Crossmembers on 16" centers	• Boxend tail
• Sealed modular wiring harness	• Air brakes
• Electric breakaway	• 12 Ton capacity
• Oil bath axle	• Electric over hydraulic
• 5' Dovetail woodcovered	• Electric over hydraulic
• 5' Ramps spring loaded	Disc Brakes
• Locking tool box	• Paver option
• Rubber mounted lights	

### Dimensions

Length	A	B	C	D	E	Dove
25'	300"	190.5"	68.5"	34"	102"	60"
29'	348"	214.5"	68.5"	34"	102"	60"
33'	396"	238.5"	68.5"	34"	102"	60"

