



Commercial Series TA15TC Tagalong Series Pierced Frame

<ul style="list-style-type: none"> • G.V.W.R. - 30,000 # • G.A.W.R. (Each Axle) - 15,500 # • Coupler -3 position pintle ring • Safety Chain -7/16 grade 70 with hooks • Jack -25,000 # 2 speed landing gear • Frame -14" @ 26 # I-beam • Crossmembers -5" channel on 16" center • Side rails - 8"channel with (10) D-rings 	<ul style="list-style-type: none"> • Axles - 2 Dexter 15,500 # dual wheel Electric brake axles oil bath • Suspension - slipper spring • Tires -ST215/75R/17.5" load range H • Wheel - 6.75 x 17.5" 10 bolt disk • Deck - 2" oak • Lights - D.O.T. stop, tail, turn, and clearance • Elec. Plug -7-way Semi type • Paint - High solids acrylic enamel
--	--

Standard Features

Optional Features

<ul style="list-style-type: none"> • Sealed modular wiring harness • Oil bath axles • 5' Dovetail • 5' Ramps spring loaded • Locking tool box • Rubber mounted lights 	<ul style="list-style-type: none"> • Dual jacks • 6' Dove tail • Spare tire mount
---	--

Dimensions

Length	A	B	C	D	E
25'	300"	189.5"	69"	36.75"	102"
29'	348"	213.5"	69"	36.75"	102"
33'	396"	237.5"	69"	36.75"	102"

