



Commercial Series

TA20TC Tagalong Series

• G.V.W.R. - 45,000 #	• Axles - 2 Dexter 22,500 # dual wheel air brake axles with spring break
• G.A.W.R. (Each Axle) - 22,500 #	• Suspension - Heavy duty hutch 9700
• Coupler -3 position pintle ring	• Tires -215-75R-17.5" load range H
• Safety Chain -7/16 grade 70 with hooks	• Wheel - 6.75 x 17.5" 10 bolt disk
• Jack -25,000 # 2 speed landing gear	• Deck - 2" oak
• Frame -14" @ 26 # I-beam	• Lights - D.O.T. Stop, tail, turn, and clearance
• Crossmembers -5" channel on 16" center	• Elec. Plug -7-way Semi type
• Side rails - 8"channel with (5) D-rings per side	• Paint - High solids acrylic enamel

Standard Features

Optional Features

• ABS on one axle	• Dual jacks
• Spring brakes both axles	• 6' Dove tail
• Sealed modular wiring harness	• Spare tire mt.
• Internal to air and emergency relay valve	
• Oil bath axles	
• 5' Dovetail	
• 5' Ramps spring loaded	
• Locking tool box	
• Rubber mounted lights	

Dimensions

Length	A	B	C	D	E
25'	300"	189.5"	69"	36.75"	96"
29'	348"	213.5"	69"	36.75"	96"
33'	396"	237.5"	69"	36.75"	96"

