



## 6 T Equipment Series

• G.V.W.R.-12,000 #	• Axles - 2-6,000 # cambered brake axles
• G.A.W.R.(Each Axle) - 6,000 #	• Suspension - slipper spring with equalizer
• Coupler - 2 - 5/16" adjustable	• Tires - ST 235 / 80R 16" load range E
• Safety Chain - 3/8" grade 43 with hooks	• Wheel -16" 8 bolt white spoke
• Jack -10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 6" channel	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 3" channel	• Elec. Plug - 7-way RV
• Fenders - 10"x72" diamond plate with backs	• Paint - High solids acrylic enamel
• Tongue - 6" channel wrap around	• 4' Ramps
• Bed width - 81"	• Sealed modular wiring harness

### Standard Features      Optional Features

• 16" white spoke	• Side rails
• Pressure treated decking	• Steel deck
• Light protectors	• Double-split gate w/ springs
• Electric breakaway	• Self Cleaning Dovetail
• E-Z Lube axles	• D-Rings
	• 5' ramps

### Dimensions

Weight / Length	A	B	C	D	E	Dove
2,600Lbs / 12'	144"	88"	46.5"	25.5"	82"	24"
2,650Lbs / 14'	168"	100"	46.5"	25.5"	82"	24"
2,700Lbs / 16'	192"	112"	46.5"	25.5"	82"	24"
2,750Lbs / 18'	216"	124"	46.5"	25.5"	82"	24"
2,800Lbs / 20'	240"	136"	46.5"	25.5"	82"	24"
2,875Lbs / 22'	264"	148"	46.5"	25.5"	82"	24"

