



EQ8206T Equipment

<ul style="list-style-type: none"> • G.V.W.R.-12,000 # • G.A.W.R.(Each Axle) - 6,000 # • Coupler - 2 - 5/16" adjustable • Safety chain - 3/8 grade 43 with hooks • Jack -10,000 # drop leg • Frame - 6" channel • Crossmembers - 3" channel • Drive over Fenders diamond plate with backs • Tongue - 6" channel full frame • Bed width -102" including rub rail • Side rails - 6" channel with stake pockets 	<ul style="list-style-type: none"> • Axles - 2-6,000 # cambered brake axles • Suspension - Slipper spring with equalizer • Tires - ST 235 / 80R 16" load range E • Wheel -16" 8 bolt white spoke • Deck - 2" pressure treated pine • Lights - D.O.T. stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel • Ramps - 5' • Sealed modular wiring harness
---	--

Standard Features

Optional Features

<ul style="list-style-type: none"> • 16" White spoke • Pressure treated decking • Drive over fenders • Electric breakaway • E-Z Lube brake axles 	<ul style="list-style-type: none"> • Steel deck dove tail • D-Rings • Gooseneck
---	--

Dimensions

Weight / Length	A	B	C	D	E	Dove
3,750Lbs / 20'	240"	136"	46"	30"	102"	36"
3,850Lbs / 22'	264"	148"	46"	30"	102"	36"

