



Gooseneck 10 Ton Workhorse Series Pierced Frame

• G.V.W.R. - 25,000 #	• Axles - 2 Dexter 10,000# dual wheel electric brake axles
• G.A.W.R.(each Axle) - 10,000 #	• Suspension - Multi-leaf slipper spring with equalizer
• Coupler - 2 5/16" adjustable	• Wheel - 6.75 x 16" dual 8 bolt
• Safety Chain-3/8" grade 43 with hooks	• Tires - ST 235/ 80R16" load range E
• Jacks - dual 10,000 # drop leg side crank	• Deck - 2" pressure treated pine
• Frame -12" I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers -3" structural channel	• Elec. Plug - 7-way RV
• Side rails - 6" channel with stake pockets and rub rails	• Paint - High solid acrylic enamel
• * Frame - 12 @ 19 I-beam 31' and up	

Standard Features

Optional Features

• Spare tire rack	• Steel deck
• Crossmembers on 16" centers with pierced frame	• Deck over neck
• Sealed modular wiring harness	• 12 ton capacity
• Electric breakaway	• Electric over hydraulic
• Oil bath Axles	• Headache rack
• 5' Self cleaning dovetail	• Center pop-up dovetail with gas spring assist.
• Deck level ramps	• 5th wheel
• Rubber mt. lights	• Anti twist pipe
• Spare tire mt.*Gooseneck only	
• Keyed security lock for storage box	

Dimensions

Weight / Length	A	B	C	D	E	Dove
6,200Lbs / 25'	300"	192"	91"	34"	102"	60"
6,375Lbs / 29'	348"	207"	91"	34"	102"	60"
6,550Lbs / 31'	372"	224"	91"	34"	102"	60"
6,750Lbs / * 33'	396"	240"	91"	34"	102"	60"
6,950Lbs / * 35'	420"	272"	91"	34"	102"	60"

