



Gooseneck 7 Ton Series

| | |
|---|---|
| • G.V.W.R. - 14,000 # | • Axles - 2 Dexter 7,000# single wheel electric brake axles |
| • G.A.W.R.(Each Axle) - 7,000 # | • Suspension-Multi-leaf spring w/equalizer |
| • Coupler - 2-5/16" adjustable | • Tires - 235-80R-16" load range E |
| • Safety Chain - 3/8" grade 43 with hooks | • Wheel - 6.75 x 16" 8 bolt white spoke |
| • Jack -10,000 # drop leg | • Deck - 2" pressure treated pine |
| • Frame-12" I-beam | • Lights - D.O.T. stop, tail, turn, and clearance |
| • Crossmembers - 3" channel on 16" center | • Elec. Plug - 7-way RV |
| • Siderails - 6" channel w/stake pockets /rub rails | • Paint - High solids acrylic enamel |
| • Locking toolbox in neck | |

Standard Features Optional Features

| | |
|---------------------------------|---------------------------|
| • Crossmembers on 16" centers | • Dual jacks |
| • Sealed modular wiring harness | • Steel deck |
| • Electric breakaway | • Deck over neck |
| • E-Z Luble axles | • 5th wheel option |
| • 5' dovetail | • Electric over hydraulic |
| • 5' ramps | • Headache rack |
| • Spare tire mount | • Popup dovetail |

Dimensions

| Weight / Length | A | B | C | D | E | Dove |
|-----------------|------|------|-----|-----|------|------|
| 5,700Lbs / 25' | 300" | 178" | 91" | 37" | 102" | 60" |
| 5,850Lbs / 29' | 348" | 226" | 91" | 37" | 102" | 60" |

