



GEQ6T Series

• G.V.W.R.-12,000 #	• Axles - 2-6,000 # cambered brake axles
• G.A.W.R.(Each Axle) - 6,000 #	• Suspension - slipper spring with equalizer
• Coupler - 2 - 5/16" adjustable gooseneck	• Tires - ST 235 / 80R16 load range E
• Safety Chain - 3/8" grade 43 with hooks	• Wheel -16" 8 bolt white spoke
• Jack -10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 6" channel	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 3" channel	• Elec. Plug - 7-way RV
• Fenders - 10"x72" diamond plate with backs	• Paint - High solids acrylic enamel
• 8" Channel gooseneck	• 4' Ramps
• Bed width -82"	• Sealed modular wiring harness

Standard Features

Optional Features

• 16" white spoke	• Side rails
• Pressure treated decking	• Steel deck
• Light protectors	• 48" split gate
• Electric breakaway	• Dual jacks
• E-Z Lube axles	• D-Rings
• Spare tire mount	• Self cleaning dovetail

Dimensions

Weight / Length	A	B	C	D	E	Dove
3,050Lbs / 16'	192"	136"	91"	28.25"	82"	24"
3,150Lbs / 18'	216"	148"	91"	28.25"	82"	24"
3,250Lbs / 20'	240"	160"	91"	28.25"	82"	24"
3,350Lbs / 22'	264"	172"	91"	28.25"	82"	24"
3,450Lbs / 24'	288"	184"	91"	28.25"	82"	24"

