



Gooseneck 10T Hydraulic Dove Series Pierced Frame

• G.V.W.R. - 25,900 #	• Axles - 2 Dexter 10,000 # dual wheel electric brake axles
• G.A.W.R.(Each Axle) - 10,000#	• Suspension - multi-leaf slipper spring
• Coupler -adjustable gooseneck	• Tires - ST235/80R/16" load range E
• Safety chain -3/8" grade with hooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jack-10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame -12" I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 4" channel	• Elec. Plug - 7-way RV
• Side rails - 8" channel with 10/ D-rings	• Paint - High solids acrylic enamel
• HYD Dove Lift Capacity 10,000 lbs	

Standard Features

Optional Features

• 16" dual wheels	• 12 ton capacity
• Crossmembers on 16" centers	• Electric over hydraulic
• Sealed modular wiring harness	• Headache rack
• Electric breakaway	• Electric over hydraulic disc brakes
• Oil bath axle	• Double two speed jacks
• 9' Hyd dovetail	• Deck over neck
• Locking tool box	
• Rubber mounted lights	
• Spare tire rack	

Dimensions

Weight / Length	A	B	C	D	E	Dove
8,400Lbs / 31'	372"	223"	91"	34"	102"	108"
8,600Lbs / 33'	396"	235"	91"	34"	102"	108"
8,800Lbs / 35'	420"	247"	91"	34"	102"	108"
9,200Lbs / 40'	480"	313"	91"	34"	102"	108"

