



Commercial Series Gooseneck 10 TC Series Pierced Frame

• G.V.W.R. - 22,500 #	• Axles - 2 Dexter 10,000 # dual wheel electric brake axles
• G.A.W.R.(Each Axle) -10,000#	• Suspension - Multi-leaf slipper spring
• Coupler -adjustable gooseneck	• Tires - ST235/80R/16" load range D
• Safety Chain -3/8" grade 43 withhooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jack-10,000 # drop leg	• Deck - 2" oak
• Frame -12" @ 19# I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 4" channel on 16" center	• Elec. Plug - 7-way RV
• Side rails - 8" channel with (10) D rings	• Paint - high solids acrylic enamel

Standard Features

Optional Features

• 16" dual wheels	• Dual jacks
• Crossmembers on 16" centers	• Boxend tail
• Sealed modular wiring harness	• Spring loaded ramps
• Electric breakaway	• 12 ton capacity
• Oil bath axle	• Electric over hydraulic
• 5' dovetail	• Wood covered ramps
• 5' ramps spring loaded	• Headache rack
• Locking tool box	• Electric over hydraulic disc brakes
• Rubber mounted lights	
• Spare tire rack	

Dimensions

Length	A	B	C	D	E
25'	297"	190"	91"	34"	102"
29'	345"	214"	91"	34"	102"
31'	372"	226"	91"	34"	102"
33'	393"	250"	91"	34"	102"
35'	420"	262"	91"	34"	102"
38'	456"	274"	91"	34"	102"
40'	468"	286"	91"	34"	102"

