



Commercial Series

10TC Gooseneck Tilt Series

<ul style="list-style-type: none"> • G.V.W.R. - 20,000 # • G.A.W.R.(Each Axle) - 10,000 # • Coupler - 2 5/16" adjustable • Safety Chain - 3/8 grade 43 withhooks • Jack - 10,000 # drop leg • Frame -12 @ 19 # I-beam • Crossmembers - 4" channel on 16" center • Side rails - 8" channel with 10 D-Rings on 24" center • Approach plate for easy loading 	<ul style="list-style-type: none"> • Axles - 2 Dexter 10,000# dual wheel electric brake axles • Suspension - Multi-leaf slipper spring w-equalizer • Tires - 235-80R-16" load range D • Wheel - 6.75 x 16" dual 8 bolt • Deck - 2" pressure treated pine • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel
--	---

Standard Features

Optional Features

<ul style="list-style-type: none"> • 16" dual wheels • Crossmembers on 16" centers • Sealed modular wiring harness • Electric breakaway • Oil bath axles • Rubber Mt. lights • Spare tire rack 	<ul style="list-style-type: none"> • Dual jacks • Steel deck • Deck over neck • 12 Ton capacity • Vacuum over hydraulic • Electric over hydraulic • Electric over hydraulic disc brakes
---	--

Dimensions

Length	A	B	C	D	E
25'	300"	151"	91"	38.5"	96"
29'	348"	175"	91"	38.5"	96"

