



## *LS Utility Series*

|  |   |
|--|---|
| • G.V.W.R. - 2,900 #                       | • Axle - 3,500 # cambered E-Z lube                |
| • G.A.W.R. - 3,500 #                       | • Suspension - Multi-leaf spring                  |
| • Coupler - 2"                             | • Tires - 205-75-15" load range C                 |
| • Safety Chain - 3/16" grade 30 with hooks | • Wheel - 15" 5 bolt white spoke                  |
| • Jack - top wind                          | • Deck - 2" pressure treated pine                 |
| • Frame - 3"x2"x 3/16" angle               | • Lights - D.O.T. stop, tail, turn, and clearance |
| • Crossmembers - top 3"x2"x 3/16 angle     | • Elec. Plug - 4-way flat                         |
| • Fenders - 9"x32" roll formed with backs  | • Paint - High solids acrylic enamel              |
| • Deck height 20"                          |   |

### *Standard Features      Optional Features*

|                             |                        |
|-----------------------------|------------------------|
| • 15" white spoke rims      | • 24" sides            |
| • Pressure treated decking  | • Expanded metal sides |
| • Light protectors          | • Slatted sides        |
| • E-Z Lube axle             | • Swing up jack        |
| • Gate 48" with Gas Springs | • Chrome wheels        |

### *Dimensions*

| Weight / Length  | A    | B     | C     | D   | E   |
|------------------|------|-------|-------|-----|-----|
| 750Lbs / 5X8'    | 96"  | 55.5" | 38.5" | 20" | 60" |
| 800Lbs / 5X10'   | 120" | 69.5" | 38.5" | 20" | 60" |
| 850Lbs / 5X12'   | 144" | 86.5" | 38.5" | 20" | 60" |
| 900Lbs / 5X14'   | 168" | 98.5" | 38.5" | 20" | 60" |
| 975Lbs / 6X10'   | 120" | 69.5" | 38.5" | 20" | 76" |
| 1,050Lbs / 6X12' | 144" | 86.5" | 38.5" | 20" | 76" |
| 1,125Lbs / 6X14' | 168" | 100"  | 38.5" | 20" | 76" |

