



SS Utility Series

• G.V.W.R. - 2,900 #	• Axle - 3,500 # cambered E-Z lube
• G.A.W.R. - 3,500 #	• Suspension - multi-leaf spring
• Coupler - 2"	• Tires - 205-75-15" load range C
• Safety chain - 3/16" grade 30 with hooks	• Wheel - 15" 5 bolt white spoke
• Jack - top wind	• Deck - 2" pressure treated pine
• Frame - 3"x2"x 3/16" angle	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 3"x2"x3/16 angle	• Elec. Plug - 4-way flat
• Fenders - 9"x32" roll formed with backs	• Paint - high solids acrylic enamel
• Deck height 20"	

Standard Features Optional Features

• 15" white spoke rims	• Swing up jack
• Pressure treated decking	• Radial Up grade
• Light protectors	• Chrome wheels
• E-Z Lube axle	• Brake axle
• 2' sides	• 5' Wide Double fold gate
• Gate length 48"	• 6' Wide Double fold gate

Dimensions

Weight / Length	A	B	C	D	E
990Lbs / 5X10'	120"	69.5"	38.5"	20"	60"
1,160Lbs / 6X10'	120"	69.5"	38.5"	20"	76"
1,225Lbs / 6X12'	144"	86.5"	38.5"	20"	76"

