



## *EQ8206T Equipment*

<ul style="list-style-type: none"> <li>• G.V.W.R.-12,000 #</li> <li>• G.A.W.R.(Each Axle) - 6,000 #</li> <li>• Coupler - 2 - 5/16" adjustable</li> <li>• Safety chain - 3/8 grade 43 with hooks</li> <li>• Jack -10,000 # drop leg</li> <li>• Frame - 6" channel</li> <li>• Crossmembers - 3" channel</li> <li>• Drive over Fenders diamond plate with backs</li> <li>• Tongue - 6" channel full frame</li> <li>• Bed width -102" including rub rail</li> <li>• Side rails - 6" channel with stake pockets</li> </ul>	<ul style="list-style-type: none"> <li>• Axles - 2-6,000 # cambered brake axles</li> <li>• Suspension - Slipper spring with equalizer</li> <li>• Tires - ST 235 / 80R 16" load range E</li> <li>• Wheel -16" 8 bolt white spoke</li> <li>• Deck - 2" pressure treated pine</li> <li>• Lights - D.O.T. stop, tail, turn, and clearance</li> <li>• Elec. Plug - 7-way RV</li> <li>• Paint - High solids acrylic enamel</li> <li>• Ramps - 5'</li> <li>• Sealed modular wiring harness</li> </ul>
---	--

### *Standard Features*

### *Optional Features*

<ul style="list-style-type: none"> <li>• 16" White spoke</li> <li>• Pressure treated decking</li> <li>• Drive over fenders</li> <li>• Electric breakaway</li> <li>• E-Z Lube brake axles</li> </ul>	<ul style="list-style-type: none"> <li>• Steel deck dove tail</li> <li>• D-Rings</li> <li>• Gooseneck</li> </ul>
---	--

### *Dimensions*

Weight / Length	A	B	C	D	E	Dove
3,750Lbs / 20'	240"	136"	46"	30"	102"	36"
3,850Lbs / 22'	264"	148"	46"	30"	102"	36"

